



No.180 スプロケット

P = 57.15m/m(2-1/4")



BW形



CW形

(単位 : mm)

歯数	ピッチ径 P.C.D.	外径 O.D.	BW形					CW形						
			軸穴径H.D.		ボス		概略重量 kg	材質	軸穴径HD		ボス		概略重量 kg	材質
			最小	最大	径B.D	長さB.L			最小	最大	径B.D	長さB.L		
11	202.85	229	43	85	135	75	12.5							
12	220.81	248	48	95	150	75	14.6							
13	238.81	266	58	105	170	80	17.8							
14	256.83	285	58	115	180	80	20.9							
15	274.87	303	58	115	180	80	22.8							
16	292.94	322	58	115	180	80	24.9							
17	311.01	340	58	115	180	80	27.1							
18	329.11	358	58	115	180	80	30.1							
19	347.21	377						68	120	190	85	33.6		
20	365.33	395						68	120	190	85	37.2		
21	383.45	413						68	120	190	85	39.2		
22	401.57	432						68	120	190	85	41.7		
23	419.71	450						68	120	190	85	45.1		
24	437.84	468						68	120	190	85	48.2		
25	455.99	487						68	120	190	85	52.2		
28	510.43	541						68	125	200	90	64.3		
30	546.74	578						78	135	215	110	78.7		
35	637.56	669						78	135	215	110	101.0		
40	728.41	760						78	135	215	110	126.0		
45	819.28	852						78	135	230	125	162.0		
50	910.17	943						78	135	230	125	193.0		

* 全品焼入れなし

* BW形の歯数11~18、CW形の歯数19~50のものは溶接タイプ・材質は普通鋼